# **F-PACE**

TECHNICAL SPECIFICATION DECEMBER 2022

# JAGUAR

POWERTRAIN	D200 MHEV	D300 MHEV	
Transmission	Automatic	Automatic	
Driveline	AWD AWD		
Maximum power (PS/kW/rpm)	204/150/3,750-4,000	300/221/4,000	
Maximum torque (Nm/rpm)	430/1,750-2,500	650/1,500-2,500	
Capacity (cc)	1,997	2,996	
No. of cylinders/Valves per cylinder	4/4	6/4	
Cylinder layout	Inline	Inline	
Bore/stroke (mm)	83/92.31	83/92.31	
Compression ratio (:1)	16.5	15.5	
PERFORMANCE			
Acceleration (secs) 0-60mph (0-100km/h)	7.8 (8.2)	6.1 (6.4)	
Maximum speed mph (km/h)	130 (210) 143 (230)		
BRAKES			
Front type	Single Piston Sliding Caliper, Vented Disc		
Front diameter (mm)	350 370		
Rear type	Single Piston Sliding Caliper, Vented Disc		
Rear diameter (mm)	325 325		
Park Brake	iEPB, motor on caliper		

Some features may vary between optional and standard for different model years and due to the impact of Covid-19, many of our images have not been updated to reflect 23/24 model year specifications. Please refer to the car configurator and additionally consult your local Retailer for detailed 23/24 model year specifications and do not base an order on imagery alone. Jaguar Land Rover Limited is constantly seeking ways to improve the specification, design and production of its vehicles, parts and accessories and alterations take place continually, and we reserve the right to change without notice.

WEIGHTS (kg)*		D200 MHEV	D300 MHEV		
Unladen weight (EU)**		1,951	2,083		
Unladen weight (DIN)†			1,876	2,008	
Gross Vehicle Weight (	GVW)		2,540	2,660	
TOWING (kg)					
Unbraked trailer			750	750	
Maximum towing			2,400	2,400	
Maximum coupling poi	nt (nose weight)		100	100	
Maximum vehicle and t	railer combination		4,940	5,060	
ROOF CARRYING (kg)					
Maximum roof load (including cross bars)		75	75		
FUEL ECONOMY					
Fuel tank capacity - us	eable litres		62	68	
Diesel/Gasoline Particulate Filter (DPF/GPF)					
WLTP <sup>++</sup>					
	Low	mpg (l/100km)	38.7 - 36.2 (7.3 - 7.8)	27.4 - 25.2 (10.3 - 11.2)	
	Medium	mpg (l/100km)	45.6 - 42.2 (6.2 - 6.7)	37.2 - 36.2 (7.6 - 7.8)	
WLTP Consumption	High	mpg (l/100km)	51.4 - 47.9 (5.5 - 5.9)	49.6 - 46.3 (5.7 - 6.1)	
	Extra High	mpg (l/100km)	42.2 - 39.2 (6.7 - 7.2)	39.2 - 37.2 (7.2 - 7.6)	
	Combined	mpg (l/100km)	44.8 - 41.5 (6.3 - 6.8)	39.2 - 36.7 (7.2 - 7.7)	
WLTP CO <sub>2</sub> Emissions	Combined	(g/km)	166 - 178	189 - 201	

#### Standard.

0300	MHEV
<b>D</b> 300	

<sup>\*</sup>Weights reflect vehicles to standard specifications. Optional extras increase weight. \*\*Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel. †The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO<sub>2</sub> and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted.

POWERTRAIN	P250	P400 MHEV	P400e PHEV	P550 SVR
Transmission	Automatic	Automatic	Automatic	Automatic
Driveline	AWD	AWD	AWD	AWD
Maximum power (PS/kW/rpm)	250/184/5,500	400/294/5,500-6,500	404/297/5,500*	550/405/6,250-6,500
Maximum torque (Nm/rpm)	365/1,300-4,500	550/2,000-5,000	640/1,500-4,400*	700/3,500-5,000
Capacity (cc)	1,997	2,995	1,997	5,000
No. of cylinders/Valves per cylinder	4/4	6/4	4/4	8/4
Cylinder layout	Inline	Inline	Inline	Longitudinal V
Bore/stroke (mm)	83/92.29	83/92.29	83/92.29	92.5/93
Compression ratio (:1)	10.5	10.5	9.5	9.5
PERFORMANCE				
Acceleration (secs) 0-60mph (0-100km/h)	6.9 (7.3)	5.1 (5.4)	5.0 (5.3)	3.8 (4.0)
Maximum speed mph (km/h)	135 (217)	155 (250)	149 (240)	178 (286)
ELECTRIC MOTOR DATA				
Maximum Power PS (kW)	_	_	143 (105)	_
Maximum Torque (Nm)	_	_	275	_
BRAKES				
Front type	Sin	gle Piston Sliding Caliper, Vented	Disc	BREMBO Opposed piston 4 pistons 4x42mm Low Met Copper free pad
Front diameter (mm)	350	370	370	395
Rear type	Sin	gle Piston Sliding Caliper, Vented	Disc	CONTINENTAL Single piston 42mm sliding caliper with integrated parking brake Low Met Copper free pad
Rear diameter (mm)	325	325	325	396
Park Brake		iEPB, motor on caliper		CONTINENTAL integrated parking brake

- Not available.

\*When combined with electric motor.

BATTERY AND CHARGING TIMES	P250	P400 MHEV	P400e PHEV	P550 SVR
Home Charger/Wall box 7kW	_	_	2 hours 16 mins to 100%	-
DC Charger 50kW	_	_	30 mins to 80% / 1 hour 13 mins to 100%	_
Domestic Plug 2.3kW	_	-	7 hours 6 mins to 100%	-
Battery capacity Total (Usable) kWh	_	_	13.6	-
Charging cable length (m)	_	-	5	_
WEIGHTS (kg)*				
Unladen weight (EU)**	1,897	2,028	2,189	2,133
Unladen weight (DIN) <sup>+</sup>	1,822	1,953	2,114	2,058
Gross Vehicle Weight (GVW)	2,520	2,600	2,690	2,590
TOWING (kg)				
Unbraked trailer	750	750	750	750
Maximum towing	2,400	2,400	2,000	2,400
Maximum coupling point (nose weight)	100	100	100	100
Maximum vehicle and trailer combination	4,920	5,000	4,740	4,990
ROOF CARRYING (kg)				
Maximum roof load (including cross bars)	75	75	75	75
FUEL ECONOMY				
Fuel tank capacity – useable litres	83	83	69	83
Diesel/Gasoline Particulate Filter (DPF/GPF)				

■ Standard – Not available.

\*Weights reflect vehicles to standard specifications. Optional extras increase weight. \*\*Includes a 75 kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel.

WLTP*			P250	P400 MHEV	P400e PHEV	P550 SVR
EV Range TEL	Combined	miles/km	-	_	40/65	_
	Low	mpg (l/100km)	23.0 - 21.6 (12.3 - 13.1)	19.9 - 19.1 (14.2 - 14.8)	-	14.7 (19.2)
	Medium	mpg (l/100km)	32.1 - 29.7 (8.8 - 9.5)	30.1 - 28.5 (9.4 - 9.9)	-	24.1 (11.7)
WLTP Consumption	High	mpg (l/100km)	36.2 - 33.6 (7.8 - 8.4)	35.3 - 33.2 (8.0 - 8.5)	-	27.7 (10.2)
	Extra High	mpg (l/100km)	30.4 - 28.8 (9.3 - 9.8)	31.0 - 29.1 (9.1 - 9.7)	-	25.4 (11.1)
	Combined	mpg (l/100km)	30.7 - 29.1 (9.2 - 9.7)	29.7 - 28.0 (9.5 - 10.1)	176.6 - 156.9 (1.6 - 1.8)	23.5 (12.0)
WLTP CO <sub>2</sub> Emissions	Combined	(g/km)	209 - 222	217 - 230	37 - 41	274

- Not available.

\*The figures provided are as a result of official manufacturer's tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO<sub>2</sub>, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

# **F-PACE** - DIMENSIONS

Vehicle Height - 1,664 mm (1,670 mm on SVR)

#### Headroom

Maximum front/rear headroom with Panoramic roof fitted 960/952 mm Maximum front/rear headroom with standard roof 1,007/977 mm

#### Legroom

Maximum front legroom 1,023 mm Maximum rear legroom 944 mm

#### Loadspace Capacity

Height 813 mm, Width 1,091 mm Loadspace width between arches 1,048 mm Maximum loadspace volume behind first row Dry\* Up to 1,440 litres, Wet\*\* Up to 1,842 litres Maximum loadspace volume behind second row Dry\* Up to 613 litres, Wet\*\* Up to 793 litres

#### **Turning Circle**

Kerb-to-kerb 11.95 m (12.01 m on SVR) Wall-to-wall 12.39 m (12.29 m on SVR) Turns lock-to-lock 2.52

**Overall Width** (inc. mirrors) 2,175 mm (mirrors folded) 2,071 mm



1,640.2 mm (1,648.3 mm on SVR)



(1,665.9 mm on SVR)



\*Dry: Volume as measured with VDA-compliant solid blocks (200 mm x 50 mm x 100 mm). \*\*Wet: Volume as measured by simulating the loadspace filled with liquid. Volume measured up to the headliner. Boot configuration and total loadspace will vary by vehicle specification (model and powertrain) and market, and if full size spare or space saver spare wheel is fitted.

Dimensions were measured with vehicle at unladen weight.

4,747 mm (4,762 mm on SVR)